

Requirements for the installation of carpet, laminate or other materials in the aisles

Only flame-resistant materials in accordance with DIN 4102 / B 1 are allowed.

The appropriate test certificates of these materials must be submitted in advance for approval and must be kept available on site!

1. Upon installation of the floor covering, the obligation to make the premises safe for persons and vehicles with regards to the aisles transfers to the exhibitor. Exhibitor shall be liable for any damage. Exhibitor shall indemnify and hold harmless Messe Düsseldorf vis-à-vis third-party claims. The exhibitor shall be obligated to take out insurance.
2. All aisles must be identified clearly and visibly either through lines of tape or difference in colour as separate from the adjacent stand.
3. The exhibitor shall be responsible for the cleaning of this area.
4. No installations (and cables, pipes, lines etc.) may be laid underneath the floor covering. It is not permitted to install sound absorbing materials underneath the floor covering.

In the area of the aisles, the hall floor must not have any superstructures higher than 40 mm.
5. Height variances against the hall floor must be graduated using sloped edges with a gradient of about 3.5 ° (6 %).
6. The floor must be slip-proof and must be installed level. Smooth floor coverings may be used only if they comply with valuation group R 10 according to DIN 51 130 (see also BGR [Accident Prevention Insurance Association Regulations] 181).